



ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 10/17/2013

Revision date: 10/17/2013

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	:	ProSpec ProColor Sanded Tile Grout
Product code	:	Base 65460282 - 25lb
		Ice White 65460234 - 10lb / 65460261 - 25lb
		Bone 65460226 - 10lb / 65460248 - 25lb
		Linen 65460236 - 10lb / 65460264 - 25lb
		Oyster 65460033 - 10lb / 65460034 - 25lb
		Moonlight 65460237 - 10lb / 65460265 - 25lb
		Almond 65460222 - 10lb / 65460244 - 25lb
		Painted Desert 65460297 - 10lb / 65460269 - 25lb
		Café 65460228 - 10lb / 65460250 - 25lb
		Glacier 65460042 - 10lb / 65460043 - 25lb
		Sterling Silver 65460298 - 10lb / 65460274 - 25lb
		Winterwood 65460295 - 10lb / 65460280 - 25lb
		Antique White 65460223 - 10lb / 65460245 - 25lb
		Beach Sand 65460035 - 10lb / 65460044 - 25lb
		Sand Dollar 65460290 - 10lb / 65460273 - 25lb
		Latte 65460036 - 10lb / 65460037 - 25lb
		Warm Ivory 65460293 - 10lb / 65460281 - 25lb
		Buff 65460227 - 10lb / 65460249 - 25lb
		Delorean Gray 65460283 - 10lb / 65460255 - 25lb
		Honey 65460233 - 10lb / 65460260 - 25lb
		Pebble Brown 65460288 - 10lb / 65460270 - 25lb
		Limestone 65460286 - 10lb / 65460263 - 25lb
		Cypress 65460230 - 10lb / 65460253 - 25lb
		Dakota Prairie 65460294 - 10lb / 65460254 - 25lb
		Sahara 65460038 - 10lb / 65460039 - 25lb
		Travertine 65460242 - 10lb / 65460277 - 25lb
		Autumn 65460225 - 10lb / 65460247 - 25lb
		Khaki 65460235 - 10lb / 65460262 - 25lb
		Fawn 65460232 - 10lb / 65460258 - 25lb
		Taupe 65460241 - 10lb / 65460276 - 25lb
		Summer Wheat 65460291 - 10lb / 65460275 - 25lb
		Canyon Sunset 65460296 - 10lb / 65460251 - 25lb
		River Rock 65460289 - 10lb / 65460271 - 25lb
		Dark chocolate 65460231 - 10lb / 65460256 - 25lb
		Sable 65460240 - 10lb / 65460272 - 25lb
		Onyx Charcoal 65460229 - 10lb / 65460252 - 25lb
		Onyx Black 65460287 - 10lb / 65460268 - 25lb

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Various.

1.3. Details of the supplier of the safety data sheet

H.B. Fuller Construction Products Inc.
1105 S. Frontenac Street
Aurora, IL 60504
Phone: 1-800-552-6225

1.4. Emergency telephone number

: Medical Emergency Phone Number (24 Hours): 1-888-853-1758
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity 4 (Oral)
Skin Irritation 2
Serious Eye Damage 1
Skin Sensitization 1
Carcinogenicity 1A
Specific Target Organ Toxicity After Single Exposure 3
Specific Target Organ Toxicity After Repeated Exposure 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.

Precautionary statements (GHS-US) :

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Rinse mouth. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

Other hazards not contributing to the classification :

Not applicable.

2.4. Unknown acute toxicity (GHS-US)

ProColor Sanded Grout (*Base*): 24 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProColor Sanded Grout (*Ice White*): 83 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProColor Sanded Grout (*Sterling Silver*): 79 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProColor Sanded Grout (*Onyx Charcoal*): 76 % of the mixture consists of ingredient(s) of unknown acute toxicity.

ProColor Sanded Grout (*Bone, Linen, Oyster, Moonlight, Almond, Painted Desert, Café, Glacier, Winterwood, Antique White, Beach Sand, Sand Dollar, Latte, Warm Ivory, Buff, Delorean Gray, Honey, Pebble Brown, Limestone, Cypress, Dakota Prairie, Sahara, Travertine, Autumn, Khaki, Fawn, Taupe, Summer Wheat, Canyon Sunset, River Rock, Dark chocolate, Sable, Onyx Black*): 84 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Quartz	(CAS No) 14808-60-7	40 - 70	Acute Tox. 4 (Oral), H302 Carc. 1A, H350 STOT RE 1, H372
Cement, portland, chemicals	(CAS No) 65997-15-1	15 - 40	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
Titanium dioxide	(CAS No) 13463-67-7	1 - 5 ¹	Acute Tox. 4 (Inhalation), H332 Carc. 2, H351
Calcium oxide	(CAS No) 1305-78-8	1 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Name	Product identifier	%	GHS-US classification
Vinyl acetate	(CAS No) 108-05-4	0.5 - 1.5	Carc. 2, H351
Folpet	(CAS No) 133-07-3	< 0.1	Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 Skin Sens. 1, H317

¹ Ice White

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.
- Symptoms/injuries after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : Not available.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Firefighting instructions : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Vacuum or sweep material and place in a disposal container.

6.3. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not swallow. Avoid contact with skin and eyes. Avoid generating and breathing dust. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) ((250)/(%SiO ₂ +5) mppcf TWA (resp))
Cement, portland, chemicals (65997-15-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
Calcium oxide (1305-78-8)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Vinyl acetate (108-05-4)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear suitable waterproof gloves.

Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection : Wear suitable waterproof protective clothing.

Respiratory protection : A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Other information : Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Powder.

Colour : Various.

Odour : Characteristic.

Odour threshold : No data available.

pH : 12 - 13

Relative evaporation rate (butylacetate=1) : No data available.

Melting point : No data available.

Freezing point : No data available.

Boiling point : No data available.

Flash point : No data available.

ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: No data available.
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

VOC content : 0%, Not applicable; 0 wt, Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Incompatible materials. Moisture.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

Quartz (14808-60-7)

LD50 oral rat	500 mg/kg
---------------	-----------

Titanium dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

LD50 dermal rabbit	> 10000 mg/kg
--------------------	---------------

Calcium oxide (1305-78-8)

LD50 oral rat	500 mg/kg
---------------	-----------

Vinyl acetate (108-05-4)

LD50 oral rat	2920 mg/kg
---------------	------------

LD50 dermal rabbit	2320 mg/kg
--------------------	------------

LC50 inhalation rat (mg/l)	11400 mg/m ³ (4h)
----------------------------	------------------------------

Folpet (133-07-3)

LC50 inhalation rat (mg/l)	> 5 g/m ³ (2h)
----------------------------	---------------------------

ProSpec ProColor Sanded Tile Grout

ATE (oral)	550 – 750 mg/kg, rat
------------	----------------------

ATE (dermal)	>2000 mg/kg, rabbit
--------------	---------------------

ATE (inhalation)	No data available
------------------	-------------------

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.
Carcinogenicity : May cause cancer.

Quartz (14808-60-7)	
IARC group	1
National Toxicity Program (NTP) Status	2

Titanium dioxide (13463-67-7)	
IARC group	2B
National Toxicity Program (NTP) Status	1

Vinyl acetate (108-05-4)	
IARC group	2B

Reproductive toxicity : Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure) : May cause respiratory irritation.
Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)
Aspiration hazard : Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation : May cause respiratory tract irritation.
Symptoms/injuries after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

12.2. Persistence and degradability

ProSpec ProColor Sanded Tile Grout	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

ProSpec ProColor Sanded Tile Grout	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

ProSpec ProColor Sanded Tile Grout	
Ecology - soil	No data available.

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA

14.1. UN number

Not applicable

ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cement, portland, chemicals (65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Vinyl acetate (108-05-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 302 Threshold Planning Quantity (TPQ)	1000
--	------

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

Folpet (133-07-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

15.2. US State regulations

ProSpec ProColor Sanded Tile Grout

State or local regulations	This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	--

Quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	No

Titanium dioxide (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	No

Folpet (133-07-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	No

SECTION 16: Other information


Data sources : SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

ProSpec ProColor Sanded Tile Grout

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

- NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
- NFPA fire hazard : 1 - Must be preheated before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product