



1100 Series Four Leg Chair

Environments that Inspire Learning



18"H with
A shell

18"H with
A+ shell



Features

Seat:

- Ergonomically designed, one-piece, injection-molded, polypropylene shell with leather grain surface
- Waterfall edge promotes good circulation and relieves pressure points
- Design promotes correct seating posture. V-Back in chair provides ventilation for hips and spinal relief
- Optional seat and back pads available on 18"H chairs
- Chair with 18" A+ seat height features an extra-wide shell that provides 20% more seat surface
- Available in 7 chair sizes

Frame:

- Legs are 1 1/8" 18-gauge tubular steel
- Brackets are constructed of 13-gauge formed steel
- Nickel-plated chrome or black powdercoat finishes assure long-lasting durability
- Seat is attached to the frame on the underside of the seat with six concealed steel rivets. No exposed hardware on the surface to prevent tearing or snagging of clothes
- Chairs stack 10 to 12 high
- An optional field installed wire book basket is available for 18" high chairs



Furniture & Equipment

Visit us at www.schoolspecialty.com or call 1-888-388-3224

Specifications

Model	Shell Size	Seat Height	Chair Height	Seat Width	Seat Depth	Frame Width	Frame Depth
18" A+ 4-Leg Chair	Extra Wide	18"	32.5"	15.5"	14.5"	20"	21.5"
18" A 4-Leg Chair	Standard	18"	31"	14"	14.5"	20"	21.5"
16" 4-Leg Chair	Medium	16"	28"	12"	12"	16"	17.25"
14" 4-Leg Chair	Small	14"	23.5"	10.5"	9.5"	14.5"	17"
12" 4-Leg Chair	Small	12"	21.75"	9.5"	9.5"	14.5"	16.25"
10" 4-Leg Chair	Small	10"	19"	9.5"	9.5"	14"	14.5"
8" 4-Leg Chair	Small	8"	17"	9.5"	9.5"	13.5"	14"



Features



Secure Frame Attachment



Field Installed Wire Book Basket




Optional Seat and Back Pad


Seat Colors



Padded Seat & Back Colors





Frame Colors



Glide Options



Rubber, Ball or Felt Glides for tile and wood floors. Steel, Ball or Nylon Glides for tile and carpeted surfaces.



Furniture & Equipment

Visit us at www.schoolspecialty.com or call 1-888-388-3224



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818