

**Safety Data Sheet
Petroleum 62**

SDS Revision Date:

12/29/2014



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity	Petroleum 62
Alternate Names	Kerosine (petroleum) , Petroleum 62

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Thermco Products, Inc. 10 Millpond Drive, Unit #10 Lafayette, NJ 07848
---------------------	---------------------------------------------------------------------------------

Emergency

Customer Service: Thermco Products, Inc.	973.300.9100
-------------------------------------------------	--------------

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Combustible Liquid;H227	Combustible Liquid.
Acute Tox. 4;H312	Harmful in contact with skin.
Asp. Tox. 1;H304	May be fatal if swallowed and enters airways.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

Safety Data Sheet

Petroleum 62

SDS Revision Date:

12/29/2014



H227 Combustible liquid.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P312 Call a POISON CENTER or doctor / physician if you feel unwell.
P322 Specific measures (see information on this label).
P331 Do NOT induce vomiting.
P363 Wash contaminated clothing before reuse.

[Storage]:

P403+235 Store in a well ventilated place. Keep cool.
P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Kerosine (petroleum) CAS Number: 0008008-20-6	100	Asp. Tox. 1;H304	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Safety Data Sheet

Petroleum 62

SDS Revision Date:

12/29/2014



4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser. Apply cream.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>Classification Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.</p> <p>Additional warnings of hazards to human health and the environment: Danger of electrostatic charging. Heating or spraying may generate explosive vapor/air mixtures.</p> <p>Instructions for attending physician: Prolonged and/or repeated exposure may cause skin discomfort and inflammation (dermatitis). In case of swallowing followed by vomiting, material may be aspirated into the lungs - possibly leading to pulmonary edema (wet lung).</p> <p>Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p>
Inhalation	May be fatal if swallowed and enters airways.
Skin	Harmful in contact with skin.

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Do not use; water jet.

Safety Data Sheet Petroleum 62

SDS Revision Date:

12/29/2014



5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

5.3. Advice for fire-fighters

Fire-extinguishing agents that are unsuitable for safety reasons: Water, full spray

Special hazards arising from the substance or the preparation itself, its products of combustion or gases generated: Incomplete combustion generates carbon monoxide. Vapors are heavier than air and will spread across the ground. "Floats" up and may re-ignite.

Special protective equipment for fire-fighting:

Full-protection suit, respirator with self-contained air supply.

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Do not inhale vapors / aerosols. In case of heating up or spraying: eliminate all potential sources of ignition. Remove all personnel not required on site from danger zone. Take precautions against electrostatic charging. Seal leaks, without exposing yourself to personal risk.

Use personal protective clothing/equipment - also see item 8 -.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Try to prevent product from entering into sewer lines, bodies of water and soil. Notify fire department or police if product has entered bodies of water or sewer lines, or has contaminated soil and plants. Contain liquid by an appropriate barrier, e.g. sand, and pump into a specially marked container. Absorb any residues using absorbing materials (e.g. sand, oil binding agents and similar means of absorption). Properly dispose of in compliance with environmental regulations.

In case of inadvertent release (spillage) on waterways, keep barge, boat traffic, etc. at appropriate distance. Notify harbor/ river police, coast guard, etc. and prevent general public from getting close to the scene. If possible, seal leaks, without exposing yourself to personal risk. Contain liquid, if possible. Remove product from water surface by skimming or using suitable means of absorption. In case of spillage in rivers, etc., coordinate with competent authorities to allow product to sink to the bottom and/or use suitable deflocculation agents.

Safety Data Sheet

Petroleum 62

SDS Revision Date:

12/29/2014



7. Handling and storage

7.1. Precautions for safe handling

Handling safety instructions: Avoid skin and eye contact and wear personal protective gear. Avoid inhalation of vapors / aerosols. Inside closed rooms or when filling or emptying containers, assure sufficient ventilation during operations (use local exhaust/suction system, if needed/available). In laboratories, product should only be handled underneath exhaust fan system (GLP). Use suitable precautions to prevent product from entering sewer lines, bodies of water and soil.

Fire and explosion protection instructions: In case of heating or spraying: keep away from sources of ignition. Take precautions against electrostatic charging and explosion (see relevant chemical industry/trade association publications, e.g. BG-Chemie). Any fire protection measures required must be coordinated with competent authorities.

Miscellaneous information: Empty containers may still contain product residues and thus harbor respective risks - continue to take appropriate.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store in a cool dry area, away from heat, sparks and open flame. Keep containers sealed when not in use. Store out of direct sunlight.

Incompatible materials: Strong oxidizing agents and acids.

Suitable materials: C-steel, high-grade (stainless) steel, polyethylene, polypropylene, polyester, teflon

Unsuitable materials: Natural rubber, butyl rubber, EPDM, polystyrene

Temperature class (Germany): T 3

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

CAS No.	Ingredient	Exposure	
		Source	Value
0008008-20-6	Kerosine (petroleum)	OSHA	No Established Limit
		ACGIH	TWA: 200 mg/m ³ Skin, Revised 2003
		NIOSH	TWA 100 mg/m ³
		Supplier	No Established Limit

Safety Data Sheet Petroleum 62

SDS Revision Date:

12/29/2014



Carcinogen Data

CAS No.	Ingredient	Source	Value
0008008-20-6	Kerosine (petroleum)	OSHA Select Carcinogen: No NTP Known: No; Suspected: No IARC Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

8.2. Exposure controls

Respiratory

In case of risk that the stated boundary values may be exceeded, the following respiratory protection is recommended: filter in gas mask for org. gases and vapors (type A).

Eyes

Tightly sealing goggles with side protection.

Skin

Hydrocarbon solvent-resistant protection suit and safety shoes
Protective gloves made of Viton, e.g. Vitojekt 890 made by KCL. (permeation time > 480 min).

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

The choice of personal protective clothing depends on the hazard posed by the product, on the workplace, and on the type of handling. The suitability of protective equipment for the individual application purpose must be discussed with the manufacturer of the personal protective equipment and the government authorities. Each and every person entering the area, in which the product is handled, must wear at least protective goggles with lateral protection. Avoid exposure of the skin and eyes. Do not inhale vapors / aerosols. Do not eat, drink or smoke while working with this product. Change any wetted clothing. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance

Clear Colorless Liquid

Odor

typically

Odor threshold

Not Measured

pH

NA

Safety Data Sheet Petroleum 62

SDS Revision Date:

12/29/2014



Melting point / freezing point	< -20 C
Initial boiling point and boiling range	180/245 C
Flash Point	64 C
Evaporation rate (Ether = 1)	(ether =1) 750
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 0,6 Upper Explosive Limit: 7,0
Vapor pressure (Pa)	at 20C: 1 hPa at 50C: 5 hPa
Vapor Density	NA
Specific Gravity	at 15 C: 800,0 kg/m3
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	> 200 C
Decomposition temperature	NA
Viscosity (cSt)	Kinematic viscosity at 20C: 1,9 mm2/s
VOC %	NA
Molecular Weight	APP. 155 g/mol
hygroscopic	no
Solubility	Solubility in water at 20 C insoluble Solubility in solvents at 20 C: miscible
Distribution coefficient n-octanole/water	4,6 - > 7,0 (estimated)

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and acids.

**Safety Data Sheet
Petroleum 62**

SDS Revision Date:

12/29/2014



10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Kerosine (petroleum) - (8008-20-6)	2,835.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	4	Harmful in contact with skin.
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable

Safety Data Sheet
Petroleum 62

SDS Revision Date:

12/29/2014



Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	1	May be fatal if swallowed and enters airways.

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Kerosine (petroleum) - (8008-20-6)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

**Safety Data Sheet
Petroleum 62**

SDS Revision Date:

12/29/2014



14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification B3

US EPA Tier II Hazards

Fire: Yes
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous :
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Safety Data Sheet
Petroleum 62**

SDS Revision Date:

12/29/2014



Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

N.J. RTK Substances (>1%):

Kerosine (petroleum)

Penn RTK Substances (>1%):

Kerosine (petroleum)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: This information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Document

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity	Isoamyl Benzoate for Synthesis
Alternate Names	Isoamyl Benzoate for Synthesis

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	Chemical for synthesis
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Thermco Products, Inc. 10 Millpond Drive, Unit #10 Lafayette, NJ 07848
--------------	---------------------------------------------------------------------------------

Emergency

Customer Service: Thermco Products, Inc.	973.300.9100
------------------------------------------	--------------

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Combustible Liquid;H227 Combustible Liquid.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.
H227 Combustible liquid.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
P280 Wear protective gloves / eye protection / face protection.

[Response]:

No GHS response statements

[Storage]:

P403+235 Store in a well ventilated place. Keep cool.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
ISOPENTYL BENZOATE CAS Number: 000094-46-2	100	Not classified	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	No specific symptom data available. See section 2 for further details.
-----------------	---------------------------------------------------------------------------

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Do not inhale vapors/aerosols. Ensure supply of fresh air in enclosed rooms.

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



Hazardous decomposition: No hazardous decomposition data available.
Keep away from heat / sparks / open flames / hot surfaces - No smoking.

5.3. Advice for fire-fighters

Special risks:

Combustible. Vapors heavier than air.
Forms explosive mixtures with air on intense heating.
Development of hazardous combustion gases or vapors possible in the event of fire.

Special protective equipment for fire fighting:

Do not stay in dangerous zone without self-contained breathing apparatus.
Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. ---

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Do not inhale vapors/aerosols. Ensure supply of fresh air in enclosed rooms.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Do not inhale vapors/aerosols. Ensure supply of fresh air in enclosed rooms.
Take up with liquid-absorbent material (e.g. Chemisorb). Forward for disposal. Clean up affected area.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.
Store in a cool dry area, away from heat, sparks and open flame. Keep containers sealed when not in use. Store out of direct sunlight.

Incompatible materials: Strong oxidizing agents

Tightly closed. At +15C to +25C.

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

CAS No.	Ingredient	Exposure		Value
		Source		
0000094-46-2	ISOPENTYL BENZOATE	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	No Established Limit	
		Supplier	No Established Limit	

CAS No.	Ingredient	Carcinogen Data		Value
		Source		
0000094-46-2	ISOPENTYL BENZOATE	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

8.2. Exposure controls

- Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes** Protective safety glasses required
- Skin** Butyl rubber gloves
Layer thickness: 0.7 mm
Breakthrough time: >240 min
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



9. Physical and chemical properties

Appearance	Colorless Liquid
Odor	Almost Odorless
Odor threshold	Not Measured
pH	NA
Melting point / freezing point	NA
Initial boiling point and boiling range	260 C
Flash Point	89 C
Evaporation rate (Ether = 1)	NA
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: NA Upper Explosive Limit: NA
Vapor pressure (Pa)	NA
Vapor Density	NA
Density	0.99 g/cm ³ (@20C)
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	NA
Decomposition temperature	NA
Viscosity (cSt)	NA
VOC %	NA
Log Pow	4.15 (experimental) (Lit.)

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Forms explosive mixtures with air on intense heating.

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



10.5. Incompatible materials

Strong Oxidizing agents.

10.6. Hazardous decomposition products

No hazardous decomposition data available.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
ISOPENTYL BENZOATE - (94-46-2)	6330.00, Rat - Category: NA	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



12. Ecological information

12.1. Toxicity

Do not allow product to enter water, wastewater or soil! See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
ISOPENTYL BENZOATE - (94-46-2)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

An appreciable bioaccumulation potential is to be expected (log Po/w >3)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification B3

US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:
(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :
(No Product Ingredients Listed)

Penn RTK Substances (>1%) :
(No Product Ingredients Listed)

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is: not applicable

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: This information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Document

Ningbo Thermometer Factory : Thermometer Filling

Safety Data Sheet

Section 1: Identification

Product Name: thermometers (97-3001-97-3119,97-3130)

Manufacturer/Supplier: Ningbo Thermometer Factory

Address: Sanbanqiao Ningbo, Zhejiang 315036 China

Emergency Phone Number: 86574-87592303

Product Use: thermometers

Section 2: Hazard(s) Identification

Odor: No odor

Immediate health, physical and environmental hazards: none

Eye contact: No health effects are expected

Skin contact: No health effects are expected

Inhalation: No health effects are expected

Ingestion: No health effects are expected

Section 3: Composition/Information on Ingredients

Ingredients	C.A.S No.	% by Wt.
aviation kerosene	8008-20-6	100

Section 4: First-Aid Measures

First Aid Procedures:

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with water

Skin contact: Wash affected area with soap and water

Inhalation: No need for first air anticipated

If swallowed: Make sure all glass is removed and rinse with water.

Section 5: Fire-Fighting Measures

Flammable Properties: Flash point: 100.4 Degrees Fahrenheit

Extinguishing Media: Regular foam or Carbon Dioxide or Dry Chemical

Protection of Fire Fighters: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus.

NFPA: Flammable and Combustible Liquids Classification: Combustible Liquid Class IIIA

Unusual Fire and Explosion Hazards: Not applicable

Section 6: Accidental Release Measures

Accidental Release Measures: Steps to be taken in case material is released or spilled. Absorb with paper towel (wash hands). Thermometer contains $1/10^{\text{th}}$ of 1 cc.

Section 7: Handling and Storage

Handling: Not applicable

Storage: Not applicable

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Not applicable

Personal Protective Equipment : Eye/Face protection: Not applicable

Skin Protection: Not applicable

Respiratory Protection: Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protections

Prevention of Swallowing: Not applicable

Section 9: Physical and Chemical Properties

Specific Physical Form:	Red Liquid
General Physical Form:	Liquid
Auto-ignition Temperature:	Not applicable
Flash Point:	86 degrees Fahrenheit
Boiling Point:	356 degrees Fahrenheit
Density:	Not applicable
Vapor Pressure:	Not applicable
Specific Density:	Air=1 >5.00

Section 10: Stability and Reactivity

Stability: Stable

Materials and conditions to avoid: Strong acids, strong oxidizing agents

Section 11: Toxicological Information

Acute Oral Toxicity: no data available

Acute inhalation toxicity: no data available

Acute dermal toxicity: no data available

Section 12: Ecological Information* (non-mandatory)

- Not mandatory but keep section in document and leave empty/blank

Section 13: Disposal Considerations* (non-mandatory)

- Not mandatory but keep section in document and leave empty/blank

Section 14: Transport Information* (non-mandatory)

- Not mandatory but keep section in document and leave empty/blank

Section 15: Regulatory Information* (non-mandatory)

- Not mandatory but keep section in document and leave empty/blank

Section 16: Other Information

Disclaimer: The information contained herein is accurate to the best of our knowledge. My Company makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances.