

May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard Must Be  
 Consulted for Specific Requirements  
 IDENTITY (As Used on Label and List)  
 Frost Colored Chalk 1536

*Rec'd March 2002*

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

*001440 / 319-517*

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

**SECTION I**

Manufacturer's Name <b>DIXON TICONDEROGA</b>	Emergency Telephone Number (419) 625-9545
Address (Number, Street, City, State, and ZIP)  1706 HAYES AVENUE SANDUSKY, OHIO 44870	Telephone Number for Information (419) 625-9545
	Date Prepared #
	Signature of Preparer (optional)

**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended %Optional
--	----------	-----------	---------------------------------------

Products bearing the CP Certified Products or AP Approved Products seals of the Art and Creative Materials Institute, Inc. are certified in a program of Toxicological evaluation by a Medical expert, subject to review by the Institute's Toxicological Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans or cause acute or chronic health problems.

CONFORMS TO ASTM-4236

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

Boiling Point N/A	Specific Gravity (H <sub>2</sub> O = 1) N/A
Vapor Pressure (mm Hg) N/A	Melting Point N/A
Vapor Density (Air=1) N/A	Evaporation Rate (Butyl Acetate = 1) N/A
Solubility in Water N/A	
Appearance and Odor Assorted colors, large round tapered stick, 1" X 4", no odor.	

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media Water Spray, Foam, CO2			

Special Fire Fighting Procedures  
 Containers may be subject to ignition by fire and may release toxic or other irritating gases

Unusual Fire and Explosion Hazards  
 A self contained breathing apparatus should be used for this exposure.

(Reproduce Locally)

OSHA 174, SEPT. 1986

**SECTION V - REACTIVITY DATA**

Stability	Unstable	Conditions To Avoid	NONE
	Stable YES		
Incompatibility (Materials To Avoid)			
NONE			
Hazardous Decomposition or Byproducts As with all burning organic matter, Carbon Monoxide and other toxic fumes may be given off.			
Hazardous Polymerization	May Occur	Conditions To Avoid	NONE
	Will Not Occur YES		

**SECTION VI - HEALTH HAZARD DATA**

Route(s) Of Entry:	Inhalation?	NO	Skin?	YES	Ingestion?	YES
Health Hazards (Acute and Chronic)						
Conforms to ASTM D-4236						
Carcinogenicity:	NTP?	N/A	IARC Monographs?	N/A	OSHA Regulated?	N/A
Signs and Symptoms of Exposure						
N/A						
Medical Conditions Generally Aggravated by Exposure						
N/A						
Emergency and First Aid Procedures						
Eyes—flush with copious amounts of water and contact a physician Contact with skin—Wash area with soap and water, Ingestion—seek medical attention;						

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

Steps to Be Taken in Case Material Is Released or Spilled	Contain and place in approved containers.
Waste Disposal Method	Dispose of per all Local, State, and Federal Regulations.
Precautions to Be Taken in Handling and Storing	Do not store near heat or open flame.
Other Precautions	None

**SECTION VIII - CONTROL MEASURES**

Respiratory Protection (specify Type)				
N/A				
Ventilation	Local Exhaust	OKAY	Special	N/A
	Mechanical (General)	OKAY	Other	N/A
Protective Gloves	N/A		Eye Protection	YES
Other Protective Clothing or Equipment				
N/A				
Work/Hygenic Practices				
Contents will stain most fabrics, use of smocks, gloves, etc to protect personal clothing is suggested. Wash hands and surfaces after use.				